

## 应用规范Application NORM



公称压力: 1.6~6.4MPa

适用温度范围: -40~180℃~280℃

适用介质: 水、油、气及某些腐蚀性液体(W.O.G)

螺纹类型: G.NPT.BSPT.BSP.DIN259/2999



Working Pressure: 1000PSI

Temperature Range: -40~180℃~280℃

Suitable medium: Water, oil, air and some Corrosive liquid

Thread type: G. NPT. BSPT. BSP. DIN259/2999

## 零件及材质表 Table of parts and materials



| 零件 Part        | 材质 Material |
|----------------|-------------|
| 阀体 Body        | CF8M/CF8    |
| 球 Ball         | CF8M/CF8    |
| 阀杆 Stem        | SUS316/304  |
| 球垫 Ball gasket | PTFE        |
| 把手 Handle      | SUS304      |
| 螺帽 Screw cap   | SUS304      |

## 主要外形尺寸 Main outer size

单位 Unit mm

| DN  | G      | D   | L   | H   | w   |
|-----|--------|-----|-----|-----|-----|
| 6   | 1/4"   | 10  | 51  | 50  | 90  |
| 10  | 3/8"   | 12  | 51  | 50  | 90  |
| 15  | 1/2"   | 15  | 55  | 58  | 100 |
| 20  | 3/4"   | 20  | 66  | 62  | 120 |
| 25  | 1"     | 25  | 80  | 72  | 140 |
| 32  | 1 1/4" | 32  | 94  | 80  | 140 |
| 40  | 1 1/2" | 38  | 103 | 90  | 180 |
| 50  | 2"     | 50  | 115 | 98  | 200 |
| 65  | 2 1/2" | 64  | 160 | 125 | 220 |
| 80  | 3"     | 78  | 177 | 138 | 240 |
| 100 | 4"     | 100 | 218 | 156 | 300 |