



长半径弯头
规格 重量



E I bows
Long Radius
ASME/ANSI B16.9
MSS SP-43

Nominal Pipe Size 公称通径 inch 英寸	Dimensions		Center to End:A/B Center to Center:O Back to Face:k mm	Sch.NO.	Wall Thickness:t 壁厚		Approx. Weight 重量 90° kg
	Outside Diameter at Bevel:D 外径				t		
	inch 英寸	mm				inch 英寸	
1/2	0.840	21.3	A=38.1 B=15.7 O=76.2 K=47.8	5S 10S Std/40 40S XS/80 80S 160 XXS	0.065 0.083 0.109 0.147 0.188 0.294	1.65 2.11 2.77 3.73 4.78 7.47	0.05 0.06 0.08 0.10
3/4	1.050	26.7	A=38.1 B=19.1 O=76.2 K=50.8	5S 10S Std/40 40S XS/80 80S 160 XXS	0.065 0.083 0.113 0.154 0.219 0.308	1.65 2.11 2.87 3.91 5.56 7.82	0.06 0.08 0.11 0.14
1	1.315	33.4	A=38.1 B=22.4 O=76.2 K=55.6	5S 10S Std/40 40S XS/80 80S 160 XXS	0.065 0.109 0.133 0.179 0.250 0.358	1.65 2.77 3.38 4.55 6.35 9.09	0.08 0.13 0.16 0.20 0.25 0.26
1 1/4	1.660	42.2	A=47.8 B=25.4 O=95.3 K=69.9	5S 10S Std/40 40S XS/80 80S 160 XXS	0.065 0.109 0.140 0.191 0.250 0.385	1.65 2.77 3.56 4.85 6.35 9.70	0.21 0.24 0.26 0.35 0.42 0.64
1 1/2	1.900	48.3	A=57.2 B=28.4 O=114.3 K=82.6	5S 10S Std/40 40S XS/80 80S 160 XXS	0.065 0.109 0.145 0.200 0.281 0.400	1.65 2.77 3.68 5.08 7.14 10.15	0.17 0.26 0.37 0.50 0.65 0.93
2	2.375	60.3	A=76.2 B=35.1 O=152.4 K=106.4	5S 10S Std/40 40S XS/80 80S 160 XXS	0.065 0.109 0.154 0.218 0.344 0.436	1.65 2.77 3.91 5.54 8.74 11.07	0.28 0.45 0.66 0.90 1.33 1.61
2 1/2	2.875	73.0	A=95.3 B=44.5 O=190.5 K=131.8	5S 10S Std/40 40S XS/80 80S 160 XXS	0.083 0.120 0.203 0.276 0.375 0.552	2.11 3.05 5.16 7.01 9.53 14.02	0.55 0.80 1.29 1.79 2.33 3.43
3	3.500	88.9	A=114.3 B=50.8 O=228.6 K=158.8	5S 10S Std/40 40S XS/80 80S 160 XXS	0.083 0.120 0.216 0.300 0.438 0.600	2.11 3.05 5.49 7.62 11.13 15.24	0.80 1.17 2.04 2.74 3.83 5.25
4	4.500	114.3	A=152.4 B=63.5 O=304.8 K=209.6	5S 10S Std/40 40S XS/80 80S 120 160 XXS	0.083 0.120 0.237 0.337 0.438 0.531 0.674	2.11 3.05 6.02 8.56 11.13 13.49 17.12	1.39 2.03 3.85 5.36 6.78 8.03 10.2
5	5.563	141.3	A=190.5 B=79.2 O=381.0 K=261.9	5S 10S Std/40 40S XS/80 80S 120 160 XXS	0.109 0.134 0.258 0.375 0.500 0.625 0.750	2.79 3.40 6.55 9.53 12.70 15.88 19.05	2.82 3.45 6.51 9.27 12.1 14.7 17.6

长半径弯头
规格 重量



E I bows
Long Radius
ASME/ANSI B16.9
MSS SP-43

Nominal Pipe Size 公称通径 inch 英寸	Dimensions		Center to End:A/B Center to center:O Back to Face:k mm	Sch.NO.	Wall Thickness:t 壁厚		Approx. Weight 重量 90° kg
	Outside Diameter at Bevel:D 外径				t		
	inch 英寸	mm				inch 英寸	
6	6.625	168.3	A=228.6 B=95.3 O=7457.2 K=312.7	5S 10S Std/40 40S XS/80 80S 120 160 XXS	0.109 0.134 0.280 0.432 0.562 0.719 0.864	2.77 3.40 7.11 10.97 14.27 18.26 21.95	4.10 4.96 10.10 15.30 19.50 24.20 29.10
8	8.625	219.1	A=304.8 B=127.0 O=609.6 K=414.3	5S 10S 20 30 Std/40 40S 60 XS/80 80S 100 120 140 160 XXS	0.109 0.148 0.250 0.277 0.322 0.406 0.500 0.594 0.719 0.812 0.906 0.875	2.77 3.76 6.35 7.04 8.18 10.31 12.70 15.09 18.26 20.62 23.01 22.23	7.15 9.65 15.90 17.60 20.40 25.40 30.90 36.30 43.30 48.30 53.30 51.70
10	10.750	273.0	A=381.0 B=158.8 O=762.0 K=517.7	5S 10S 20 30 Std/40 40S XS/60 80S 80 100 120 140/XXS 160	0.134 0.165 0.250 0.307 0.365 0.500 0.594 0.719 0.844 1.000 1.125	3.40 4.19 6.35 7.80 9.27 12.70 15.09 18.26 21.44 25.40 28.58	13.70 16.70 25.00 30.50 36.10 48.80 57.30 68.60 79.50 92.80 103.00
12	12.750	323.9	A=457.2 B=190.5 O=914.4 K=619.3	5S 10S 20 30 Std/40S 40 XS/80 60 80 100 120/xxs 140 160	0.156 0.180 0.250 0.330 0.375 0.406 0.500 0.562 0.688 0.844 1.000 1.125 1.312	3.96 4.57 6.35 8.38 9.53 10.31 12.70 14.27 17.48 21.44 25.40 28.58 33.32	23.00 26.10 35.70 46.80 53.10 57.80 70.00 78.20 94.70 115.00 134.00 149.00 171.00
14	14.000	355.6	A=533.4 B=222.3 O=1066.8 K=711.2	5S 10S 10 20 Std/30S 40 XS 60 80 100 120 140 160	0.156 0.188 0.250 0.312 0.375 0.438 0.500 0.594 0.750 0.938 1.094 1.250 1.406	3.96 4.78 6.35 7.92 9.53 11.13 12.70 15.09 19.05 23.83 27.79 31.75 35.71	30.80 36.90 45.80 56.90 68.10 79.20 90.00 106.00 132.00 163.00 188.00 212.00 236.00