



2565 PN 6

DN	d1	DIN2999	D	b	k	h1	d3	d4	f	No. of Holes	d2	KG
6	10.2	R1/8	65	10	40	18	18	25	2	4	11.5	0.19
8	13.5	R1/4	70	10	45	18	22	30	2	4	11.5	0.23
10	17.2	R3/8	75	12	50	20	25	35	2	4	11.5	0.32
15	21.3	R1/2	80	12	55	20	30	40	2	4	11.5	0.37
20	26.9	R3/4	90	14	65	24	40	50	2	4	11.5	0.58
25	33.7	R1	100	14	75	24	50	60	2	4	11.5	0.73
32	42.4	R1.1/4	120	14	90	26	60	70	2	4	14.0	1.05
40	48.3	R1.1/2	130	14	100	26	70	80	3	4	14.0	1.20
50	50.3	R2	140	14	110	28	80	90	3	4	14.0	1.54
65	76.1	R2.1/2	160	14	130	32	100	110	3	4	14.0	1.87
80	88.9	R3	190	16	150	34	110	128	3	4	18.0	2.78
100	114.3	R4	210	16	170	38	130	148	3	4	18.0	3.07
150	139.7	R5	240	18	200	40	160	178	3	8	18.0	4.33
200	168.3	R6	265	18	225	44	185	202	3	8	18.0	4.81

2566 PN 16

DN	d1	DIN2999	D	b	k	h1	d3	d4	f	No. of Holes	d2	KG
6	10.2	R1/8	75	12	50	18	20	32	2	4	11	0.33
8	13.5	R1/4	80	12	55	18	25	38	2	4	11	0.39
10	17.2	R3/8	90	14	60	20	30	40	2	4	14	0.56
15	21.3	R1/2	95	14	65	20	35	45	2	4	14	0.62
20	26.9	R3/4	105	16	75	24	45	58	2	4	14	0.92
25	33.7	R1	115	16	85	24	52	68	2	4	14	1.10
32	42.4	R1.1/4	140	16	100	26	60	78	2	4	18	1.59
40	48.3	R1.1/2	150	16	110	26	70	88	3	4	18	1.77
50	60.3	R2	165	18	125	28	85	102	3	4	18	2.41
65	76.1	R2.1/2	185	18	145	32	105	122	3	4	18	3.13
80	88.9	R3	200	20	160	34	118	138	3	4	18	3.95
100	114.3	R4	220	20	180	38	140	158	3	8	18	4.38
125	139.7	R3	250	22	210	40	168	188	3	8	18	5.99
150	168.3	R4	285	22	240	44	196	212	3	8	22	7.42