

## PN10

Dismantling Joint PN10

Size	OD	D	K	b	L1	d2	Bolts Number, Diameter and Length L2
DN40	56	150	110	16	210	19	4-M16x310
DN50	66	165	125	16	210	19	4-M16x310
DN65	82	185	145	16	210	19	4-M16x310
DN80	98	200	160	16	220	19	8-M16x350
DN100	118	220	180	16	220	19	8-M16x350
DN125	144	250	210	16	220	19	8-M16x350
DN150	170	285	240	16	220	23	8-M20x360
DN200	222	340	295	17	250	23	8-M20x380
DN250	274	400	350	19	250	23	12-M20x410
DN300	326	455	400	20.5	260	23	12-M20x450
DN350	378	505	460	20.5	270	23	16-M20x450
DN400	429	565	515	20.5	270	28	16-M24x460
DN450	480	615	565	21.5	280	28	20-M24x470
DN500	532	670	620	22.5	290	28	20-M24x480
DN600	635	780	725	25	300	31	20-M27x500
DN700	738	895	840	27.5	310	31	24-M27x520
DN800	842	1015	950	30	310	34	24-M30x550
DN900	945	1115	1050	32.5	320	34	28-M30x550
DN1000	1048	1230	1160	35	330	37	28-M33x580
DN1100	1152	1340	1270	37.5	330	37	32-M33x580
DN1200	1255	1455	1380	40	350	40	32-M36x600
DN1400	1462	1675	1590	41	370	43	36-M39x640
DN1500	1565	1785	1700	42.5	390	43	36-M39x640
DN1600	1668	1915	1820	44	390	49	40-M45x680
DN1800	1875	2115	2020	47	410	49	44-M45x780
DN2000	2082	2325	2230	50	450	49	48-M45x860

Working Pressure: PN10/16/25/40.

Size: DN40-DN2000.

Coating: FBE.

Body: Ductile Iron.

End Ring: Ductile Iron.

Bolt and Nut: Steel 4.8/8.8 Galvanized

/Dacromet.

Gasket: EPDM/NBR

Working Pressure: PN10/16/25/40.

Size: DN40-DN2000.

Coating: FBE.

Body: Ductile Iron.

End Ring: Ductile Iron.

Bolt and Nut: Steel 4.8/8.8 Galvanized

/Dacromet.

Gasket: EPDM/NBR

## PN16

Dismantling Joint PN16

Size	OD	D	K	b	L1	d2	Bolts Number, Diameter and Length L2
DN40	56	150	110	16	210	19	4-M16x310
DN50	66	165	125	16	210	19	4-M16x310
DN65	82	185	145	16	210	19	4-M16x310
DN80	98	200	160	16	220	19	8-M16x350
DN100	118	220	180	16	220	19	8-M16x350
DN125	144	250	210	16	220	19	8-M16x350
DN150	170	285	240	16	220	23	8-M20x360
DN200	222	340	295	17	250	23	12-M20x380
DN250	274	400	355	19	250	28	12-M24x410
DN300	326	455	410	22.5	270	28	12-M24x450
DN350	378	520	470	23	270	28	16-M24x450
DN400	429	580	525	24	280	31	16-M27x460
DN450	480	640	585	26	280	31	20-M27x480
DN500	532	715	650	27.5	290	34	20-M30x500
DN600	635	840	770	31	310	37	20-M33x520
DN700	738	910	840	34.5	310	37	24-M33x520
DN750	792	970	900	36	310	37	24-M33x520
DN800	842	1025	950	38	320	40	24-M36x550
DN900	945	1125	1050	41.5	330	40	28-M36x550
DN1000	1048	1255	1170	45	350	43	28-M39x580
DN1100	1152	1355	1270	48.5	350	43	32-M39x580
DN1200	1255	1485	1390	52	360	49	32-M45x600
DN1400	1462	1685	1590	55	380	49	36-M45x650
DN1500	1565	1820	1710	58	410	56	36-M52x640
DN1600	1668	1930	1820	60	430	56	40-M52x700
DN1800	1875	2130	2020	65	430	56	44-M52x800
DN2000	2082	2345	2230	70	470	62	48-M56x880