

Working Pressure: PN10/16/25.

Size: DN50-DN600.

Coating: FBE.

Body: Ductile Iron.

End Ring: Ductile Iron.

**Bolt and Nut: Steel 4.8/8.8 Galvanized
/Dacromet.**

Gasket: EPDM/NBR



Size	OD Range	D	K	b	L1	Bolts Number, Diameter and Length L2
DN50	49-64	165	125	16	70	2-M12x110
DN50	59-73	165	125	16	70	2-M12x110
DN65	72-85	185	145	16	73	2-M12x120
DN80	88-103	200	160	16	76	4-M12x120
DN100	90-108	220	180	16	79	4-M12x120
DN100	99-118	220	180	16	79	4-M12x120
DN100	108-128	220	180	16	79	4-M12x120
DN125	132-146	250	210	16	79	4-M12x130
DN150	150-170	285	240	16	80	4-M12x130
DN150	158-181	285	240	16	80	4-M12x130
DN150	176-188	285	240	16	80	4-M12x130
DN200	192-209	340	295	17	84	4-M12x130
DN200	218-235	340	295	17	84	4-M12x130
DN200	218-244	340	295	17	84	4-M12x130
DN250	250-267	400	355	19	91	6-M12x140
DN250	258-280	400	355	19	91	6-M12x140
DN250	272-289	400	355	19	91	6-M12x140
DN300	290-320	455	410	20.5	91	6-M12x140
DN300	301-327	455	410	20.5	91	6-M12x140
DN300	315-332	455	410	20.5	91	6-M12x140
DN300	322-339	455	410	20.5	91	6-M12x140
DN300	332-349	455	410	20.5	115	6-M12x180
DN300	340-360	455	410	20.5	91	6-M12x140
DN350	351-368	520	470	22.5	115	8-M16x180
DN350	351-378	520	470	22.5	115	8-M16x180
DN350	374-391	520	470	22.5	115	8-M16x180
DN400	390-410	580	525	24	115	8-M16x180
DN400	400-429	580	525	24	120	8-M16x180
DN400	417-437	580	525	24	120	8-M16x180
DN400	425-442	580	525	24	120	8-M16x180
DN450	455-472	640	585	26	120	10-M16x180
DN450	476-493	640	585	26	120	10-M16x180
DN500	500-532	715	650	27.5	120	10-M16x180
DN500	527-544	715	650	27.5	120	10-M16x180
DN600	600-630	840	770	31	130	10-M16x180
DN600	630-647	840	770	31	130	10-M16x180