



GOST12836 PN10							
尺寸	D外径	D1中心距	D2突台径	水线径d2	b 厚度	孔数	单重
DN15	95	65	45	10	12	4	0.43
DN20	105	75	58	16			0.55
DN25	115	85	68	22			0.67
DN32	135	100	78	28			0.91
DN40	145	110	88	36	14	4	1.24
DN50	160	125	102	46			1.55
DN65	180	145	122	60			2.04
DN80	195	160	138	76			2.44
DN100	215	180	158	94	16	8	2.97
DN125	245	210	188	118			4.69
DN150	280	240	212	142			6.07
DN200	335	295	268	196			9.09
DN250	390	350	320	244	18	12	14.26
DN300	440	400	370	294	20		19.88
DN350	500	460	430	344	24	16	31.94
DN400	565	515	482	390	26		44.43
DN500	670	620	585	490	30	20	74.31
DN600	780	725	685	590	34		119.27
DN800	1010	950	905	780	42	24	242.06
DN1000	1220	1160	1110	980	50	28	429.64
DN1200	1455	1380	1325	1180	55	32	673.13

GOST12836 PN16							
尺寸	D外径	D1中心距	D2台径	水线径d2	b 厚度	孔数	单重
DN15	95	65	45	10	12	4	0.43
DN20	105	75	58	16			0.55
DN25	115	85	68	22			0.67
DN32	135	100	78	28			0.91
DN40	145	110	88	36	14		1.24
DN50	160	125	102	46			1.55
DN65	180	145	122	60			2.04
DN80	195	160	138	76			2.44
DN100	215	180	158	94	16	8	3.51
DN125	245	210	188	118			4.69
DN150	280	240	212	142	18		6.99
DN200	335	295	268	196	20	12	11.49
DN250	405	355	320	244	24		19.74
DN300	460	410	378	294	26		29.58
DN350	520	470	438	344	30	16	44.22
DN400	580	525	490	390	34		59.86
DN500	710	650	610	490	42	20	102.69
DN600	840	770	720	590	50		161.98
DN800	1020	950	900	78	55	24	300.6
DN1000	1255	1170	1110	980	63	28	542.16
DN1200	1485	1390	1325	1180	75	32	922.18

GOST12836 PN25							
尺寸	D外径	D1中心距	D2台径	水线径d2	b 厚度	孔数	单重
DN15	95	65	45	10	12	4	0.43
DN20	105	75	58	16			0.55
DN25	115	85	68	22			0.67
DN32	135	100	78	28			0.91
DN40	145	110	88	36	14	4	1.24
DN50	160	125	102	46			1.55
DN65	180	145	122	60	16	8	2.29
DN80	195	160	138	76	18		3.21
DN100	230	190	162	94	20		5.07
DN125	270	220	188	118	22		7.83
DN150	300	250	218	142	24		10.95
DN200	360	310	278	196	26	12	17.51
DN250	425	370	335	244	30		28.93
DN300	485	430	390	294	34	16	42
DN350	550	490	450	344	38		61.48
DN400	610	550	505	390	40		81.12
DN500	730	660	615	490	48	20	140.22
DN600	840	770	720	590	50		194.5
DN800	1075	990	930	780	63	24	409.07

GOST12836 PN40							
尺寸	D外径	D1中心距	D2台径	水线径d2	b 厚度	孔数	单重
DN15	95	65	45	10	16	4	0.63
DN20	105	75	58	16			0.8
DN25	115	85	68	22			0.98
DN32	135	100	78	28			1.38
DN40	145	110	88	36			1.49
DN50	160	125	102	46	18		2.15
DN65	180	145	122	60	20	8	3.03
DN80	195	160	138	76	22		4.08
DN100	230	190	162	94	24		6.27
DN125	270	220	188	118	28		10.31
DN150	300	250	218	142	30		14.07
DN200	375	320	280	195	38	12	28.3
DN250	445	385	345	244	45		48.5
DN300	510	450	410	294	48	16	66.99
DN350	570	510	465	344	50		88.9
DN400	655	585	535	390	56		131.59
DN500	755	670	615	490	70	20	218.77