


Silent Check Valve



No	Part	Material
1	Body	Cast iron/Ductile iron
2	Stem	Stainless steel
3	Spring	Stainless steel
4	Seat	NBR/EPDM



Description

1.Design:EN1074-3

2.Flange end:EN1092-2

3.Working Pressure:PN10 PN16

4.Size:DN50-DN400(2"-16")

DN(mm)	L(mm)	D(mm)		C(mm)		B(mm)		n-d	
		PN1.0Mpa	PN1.6Mpa	PN1.0Mpa	PN1.6Mpa	PN1.0Mpa	PN1.6Mpa	PN1.0Mpa	PN1.6Mpa
DN50	125	165		125		99		4-Φ19	
DN65	140	185		145		119		4-Φ19	
DN80	150	200		160		133		8-Φ19	
DN100	165	220		180		154		8-Φ19	
DN125	180	250		210		184		8-Φ19	
DN150	210	285		240		210		8-Φ23	
DN200	255	340		295		265		8-Φ23	12-Φ23
DN250	280	405		350	355	319		12-Φ23	12-Φ28
DN300	270	450		400	410	370		12-Φ23	12-Φ28
DN350	295	520		460	470	429		16-Φ23	16-Φ28
DN400	320	580		515	525	480		16-Φ28	16-Φ31